


THE POWER OF THE NEXT GENERATION.

THE NEW UTAX PRINTERS: JUST SWITCH THEM ON, LET THEM WARM UP AND CREATE YOUR FIRST PRINTOUT AFTER JUST NINE SECONDS. AT PRINTING SPEEDS OF BETWEEN 40 AND 60 A4 PAGES PER MINUTE, THE B/W PRINTING SYSTEMS ARE ESSENTIAL FOR FLEXIBILITY IN YOUR EVERYDAY OFFICE LIFE. CONSERVE RESOURCES AND YOUR BUDGET – AND PROTECT THE ENVIRONMENT!



An alphanumeric operation panel makes handling easier, even directly at the system.



Print anywhere – the system is accessible from anywhere in the network, even by a smartphone or laptop.



Print jobs can be released directly via network authentication with an ID card.

HIGHLIGHTS:

- ◆ **High degree of flexibility:** Different paper formats from A6R to A4, a high paper capacity of 600 to 2,600 sheets and paper weights of 60 to 220 g/m² ensure dynamic performance.
- ◆ **Maximum connectivity:** The printing systems can be quickly integrated thanks to numerous connection options such as via 10/100/1000BaseTX, WLAN, IEEE 1284 or USB 2.0.
- ◆ **Extensive storage:** The hard disk* stores large quantities of data and processes your jobs at impressive speed, without burdening the network. The systems feature new, fast SSD memory (32 GB)*, support SD cards with up to 32 GB storage space and offer system memory of 1,280 MB RAM*.
- ◆ **A fully developed security concept** thanks to the optional Data Security Kit (E) and the Policy Manager. A range of security protocols is also supported.
- ◆ **Economical operation:** The new generation of systems sets itself apart with low power consumption and wonderfully quiet operation.



Start your print jobs over the network using your smartphone or tablet with the mobile printing app – and save a lot of time. Sensitive data is encrypted and print jobs can be accessed only by authorised users after authentication or via an optional card reader. The integrated hard disk* also stores large quantities of data and processes your jobs at impressive speed, without burdening the network.



It's so simple: The user interface is structured in a clear and logical manner, ensuring a user-friendly operation. All important information can be seen immediately on the 5-line display. PIN codes can be entered quickly using a separate keypad. Long-lasting components save resources and protect the environment. – Running low on toner? Or paper? The status monitor keeps you informed, wherever you may be.



B/W-PRINTER / A4

P-4030D/DN
P-4530DN
P-5030DN
P-6030DN

P-4030D/DN P-4530DN P-5030DN P-6030DN

TECHNICAL DATA

General		General		Environment	
Type	Desktop	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac OS 10.2	Noise level	P-4030D/DN: approx. 53 dB(A) in operation, approx. 30 dB(A) in stand-by mode (ISO 7779/9296)
Function	Print	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PDF 1.5, Line Printer, IBM Proprinter X24E, EPSON LQ-850, DIABLO 630, PRESCRIBE IIe, XPS***		P-4530DN: approx. 54 dB(A) in operation, approx. 30 dB(A) in stand-by mode (ISO 7779/9296)
Print technology	Laser b/w	Functions	Duplex, private print, direct print from USB stick, PDF/XPS direct print (supports PDF 1.7), e-mail print, barcode print, 100 management codes, encryption via SSL protocol, IPv6, IPsec, IEEE 802.1x		P-5030DN: approx. 55 dB(A) in operation, approx. 30 dB(A) in stand-by mode (ISO 7779/9296)
Print format	A6R-A4, min 70 x 148 mm, max 216 x 356 mm				P-6030DN: approx. 57 dB(A) in operation, approx. 30 dB(A) in stand-by mode (ISO 7779/9296)
Print speed	P-4030D/DN: max 40 A4 pages/min, max 21 A4 pages/min in duplex P-4530DN: max 45 A4 pages/min, max 33 A4 pages/min in duplex P-5030DN: max 50 A4 pages/min, max 37 A4 pages/min in duplex P-6030DN: max 60 A4 pages/min, max 44 A4 pages/min in duplex			Safety	GS/TÜV, CE
1st page	9.0 seconds*			Options	
Warm-up time	P-4030D/DN/P-4530DN: 15 seconds P-5030DN: 20 seconds P-6030DN: 25 seconds	Dimensions/Weight		Paper feed	max 4 x PF-320 (500 sheet universal cassettes (A5-A4)), max 1 x PF-315+ (2,000 sheet large capacity cassette (A4)), PB-320 (Attachment Kit is required for PF-315+)
Print resolution	max 1,200 x 1,200 dpi	Dimensions	P-4030D/DN: 285 x 390 x 410 mm (H x W x D) P-4530DN/5030DN/6030DN: 320 x 390 x 410 mm (H x W x D)	Paper output	max 1 x PT-320 (1 x 500 sheet output tray, except P-4030D/DN)
Greyscales	256	Weight	approx. 13.5 kg (P-4030D/DN), 14.6 kg (P-4530DN/5030DN/6030DN)	Other options	HD-6 SSD (32 GB), Data Security Kit (E), Card Authentication Kit (B), Snap-in Holder, UG-33 ThinPrint® Kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, IB-32 IEEE1284 parallel, cabinet no. 67
Paper feed	1 x 500 sheet universal cassette (A6R-A4R)**, 100 sheet multi-bypass (A6R-A4R)	Environment			
Paper weights	Universal cassette 60-120 g/m², multi-bypass 60-220 g/m², duplex 60-120 g/m²	Mains voltage	220/240 V, 50 Hz		
Paper output	P-4030D/DN: 250 sheet A4 P-4530DN/5030DN/6030DN: 500 sheet A4	Power consumption	P-4030D: approx. 564 W in operation, approx. 11.5 W in stand-by mode, approx. 3 W in sleep mode P-4030DN: approx. 584 W in operation, approx. 12.1 W in stand-by mode, approx. 1.9 W in sleep mode P-4530DN: approx. 618 W in operation, approx. 13.3 W in stand-by mode, approx. 1.6 W in sleep mode P-5030DN: approx. 677 W in operation, approx. 12.8 W in stand-by mode, approx. 1.6 W in sleep mode P-6030DN: approx. 757 W in operation, approx. 13.1 W in stand-by mode, approx. 1.6 W in sleep mode		
Processor	PowerPC 465				
System memory	P-4030D: 128 MB RAM (1,152 MB RAM), 1 slot P-4030DN/4530DN/5030DN/6030DN: 256 MB RAM (1,280 MB RAM), 1 slot				
Interfaces	USB 2.0, 10/100/1000BaseTX (except P-4030D), USB host, SD card slot				
Network protocols	TCP/IP, Net BEUI, EtherTalk				

* Depending on operating status.

** P-4030D/DN: Supports only up to A5R

*** Requires additional memory.

Specifications subject to change without notice.
Image shows machine with optional accessories.

The P-4030D/DN, P-4530DN, P-5030DN and P-6030DN are manufactured in accordance with the requirements of the Energy Star Program.



UTAX GmbH has been a trade mark for professional office technology since 1961. As the partner of specialist traders and small and medium-sized businesses, we specialise in the distribution and integration of printing, copying and multifunctional systems in corporate IT. Our clients' commercial success and strategic company objectives play a central role for us. We support them with integrated document management concepts. With the MDS solution UTAX smart, output systems can be controlled irregardless of the manufacturer and the infrastructure can be optimised in line with demands.

UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trademarks of UTAX GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.

Your UTAX dealer